Point-by-point response to comments from Kristof van Oost

Understanding the role of water and tillage erosion from ²³⁹⁺²⁴⁰Pu tracer measurements using inverse modelling

5 Florian Wilken, Michael Ketterer, Sylvia Koszinski, Michael Sommer and Peter Fiener

We appreciate the input from Kristof van Oost and answered the comments and revised the manuscript accordingly. Please see the detailed answers (in italics) to the comments below:

1. It appears that the vertical redistribution of PU was not modeled but its effects are still in the measurements. Can you consider in the discussion (e.g. section 4.1) the possible effect of processes like bioturbation and colloid migration on the vertical distribution of PU?

Thanks, for this comment! The model calculates and keeps track of the vertical redistribution of ²³⁹⁺²⁴⁰Pu along the soil profile. However, this depth explicit information was not used to calculate soil redistribution. The soil redistribution calculation of both measurement and modelling data is based on the change of the inventory. Therefore, the key advantage of modelling the vertical ²³⁹⁺²⁴⁰Pu profile development is to include depletion processes at eroding sites and associated deposition of depleted sediments. As the calculations are based on inventories, a pronounced effect of bioturbation and colloid migration would require transport below the sampling depth. This might partly take place, however, Fig. 3 (measurements of high resolution depth distribution) shows a rapid decrease of the ²³⁹⁺²⁴⁰Pu activity below the plough layer at eroding sites and below 45 cm depth at most depositional sites. Therefore, we can assume that the effect of bioturbation and colloid migration has a very limited effect on the soil redistribution results and vertical profile development. We include a statement on bioturbation and colloid migration in section 4.1 as follows:

"The application of soil tracers like fallout radionuclides are based on the assumption that spatial and vertical patterns are exclusively caused by soil redistribution processes due to water and tillage erosion. Bioturbation or colloid migration can be drivers of vertical displacement, which can cause an incomplete representation of the inventory if the downward migration exceeds the soil sampling depth. Within this study, a rapid reduction of the ²³⁹⁺²⁴⁰Pu activity was found below the plough and colluvial layer of the high resolution depth profiles (see Fig. 3). Hence, there is no indication for a pronounced downward migration of ²³⁹⁺²⁴⁰Pu below the sampling depth."

2. Would the model, with a vertical discretization of 10 cm, not show significant numerical dispersion?

Thank you for pointing at this issue. The model is to some extent subject to numerical dispersion that corresponds to the vertical resolution of the profile. However, as pointed out in our answer to point 1, we calculate soil redistribution based on changes in inventories, which limits the effect of this problem. To get a grip on the sensitivity of the model to the vertical resolution, we tested a reduction of the soil layer thickness from 10 cm to 5 cm that doubled the number of soil layers. The comparison between the two vertical resolutions show a maximum difference of -1.8 Bq m^{-2} and a 25% and 75% quartile of -0.12 and 0.37 Bq m^{-2} , respectively.




Figure 1: Histogram of model difference between 10 (10 cm resolution) and 20 (5 cm resolution) soil layer vertical resolution after a simulation period of 55 yrs. The model runs were carried out using best-fit model parameterisations (please see manuscript) and a reference inventory of 43 Bq m⁻².

Based on this example, we conclude that the effect of the vertical resolution is minor and does not have a substantial impact on the results. This would be different if we would consider the migration of the ²³⁹⁺²⁴⁰Pu rich topsoil versus the ²³⁹⁺²⁴⁰Pu free subsoil. We agree that the issue of resolution was not discussed in the manuscript sufficiently and we therefore include a discussion in the text of section 4.2 as follows:

"Numerical dispersion, can affect the model results, which is related to the vertical and spatial representation of the model. The vertical soil profile representation in 10 cm increments is rather low for a fallout radionuclide tracer with a rapid decrease of 239+240Pu between the plough layer/colluvium and the subsoil layer (see Fig. 3). However, the calculation of soil redistribution is based on relative changes of the 239+240Pu inventory in relation to reference inventories. Therefore, the

sensitivity of the soil redistribution calculations on the 239+240Pu soil profile development is minor as the 239+240Pu inventory is independent from the depth distribution. The relatively high spatial resolution of 5 m x 5 m was selected to adequately represent the high landscape variability in the study area and has reliably simulated spatial patterns in previous studies (e.g. Van Oost et al., 2003; Dlugoß et al., 2012). Overall, the model performs well and explains 95% of the variance and achieves a MEF better than 0.8 in predicting 239+240Pu patterns by simulating the combined effect of three model parameters (tillage translocation coefficient, water transport capacity coefficient, water erosion strength)."

3. Does picking the 3 parameter sets for the inverse modelling (ktil, ktc and water erosion strength) imply that the model is assumed to be perfect, and that all uncertainty (model misfit, via MEF) is attributed to parameter settings?

Do you consider this a strong assumption?

The model is subject to a range of uncertainties e.g. no topography update over the past 53 yrs., short-term topographical variation (e.g. tram lines) at the time of the LIDAR measurement have a distinct effect on the simulation (for your information: we addressed this issue by applying a low pass filter), the use of a spatially homogeneous k_{til} , which might be topography related. We do not assume all of the uncertainty goes back to the parameter settings. Nevertheless, the model is able the explain up to 95% of variance (aggregated results; 45% on raster level), which is from our perspective excitingly high. To point out potential uncertainties that are related to the model, we extended the uncertainty section (4.2) as follows:

"Within this study, an inverse modelling approach was carried out to understand the contribution of soil redistribution by water and tillage erosion. The model is subject to specific uncertainties that need to be mentioned. The diffusion type equation for the tillage erosion simulation (Govers et al., 1994) follows the assumption of a spatially homogenous tillage translocation coefficient for the entire study catchment. However, as the tillage translocation coefficient is a function of tillage speed and depth, tillage translocation distances are likely to show spatial differences that may follow the topography of the study area. Furthermore, the model uses a static digital elevation model that does not account for topographical change during the simulation period, which causes static soil redistribution patterns that ignore feedback processes. This is an issue for the used digital elevation model that represents short-term topographical structures like agricultural tramlines at the acquisition time.

References:

30

35

Dlugoß, V., Fiener, P., Van Oost, K., and Schneider, K.: Model based analysis of lateral and vertical soil C fluxes induced by soil redistribution processes in a small agricultural watershed, Earth Surf. Process. Landf., 37, 193-208, 10.1002/esp.2246, 2012.

To reduce this effect, a low pass filter was applied on the digital elevation model to somewhat even out short-term structures."

- Govers, G., Vandaele, K., Desmet, P., Poesen, J., and Bunte, K.: The role of tillage in soil redistribution on hillslopes, Eur. J. Soil Sci., 45, 469-478, 10.1111/j.1365-2389.1994.tb00532.x, 1994.
- Van Oost, K., Govers, G., and Van Muysen, W.: A process-based conversion model for caesium-137 derived erosion rates on agricultural land: An integrated spatial approach, Earth Surf. Process. Landf., 28, 187-207, 2003.

Understanding the role of water and tillage erosion from ²³⁹⁺²⁴⁰Pu tracer measurements using inverse modelling

Florian Wilken^{1,2}, Michael Ketterer³, Sylvia Koszinski⁴, Michael Sommer^{4,5} and Peter Fiener²

Correspondence to: Florian Wilken (florian.wilken@usys.ethz.ch)

Abstract

10

25

Soil redistribution on arable land is a major threat for a sustainable use of soil resources. The soil redistribution process most The majority of soil redistribution studies focus on is water erosion, while wind and tillage erosion also induce pronounced redistribution of soil materials. Especially, tillage erosion is understudied, as it does not lead to visible off-site damages. The analysis of on-site / in-field soil redistribution is mostly based on tracer studies, where as radionuclide tracers (e.g. 137Cs, ²³⁹⁺²⁴⁰Pu) from nuclear weapon tests are commonly used to derive the erosion history over the past 50-60 yr. Tracer studies allow to determine soil redistribution patterns, but integrate all kinds types of soil redistribution processes and hence do not allow to unravel the contribution of different-individual erosion processes. The aim of this study is to understand the contribution of water and tillage erosion leading to soil patterns found in a small hummocky ground moraine kettle hole catchment under intensive agricultural use. Therefore, ²³⁹⁺²⁴⁰Pu derived soil redistribution patterns were analysed using an inverse modelling approach accounting for water and tillage erosion processes. The results of this analysis clearly point out that tillage erosion is the dominant process of soil redistribution in the smallstudy catchment, which also affects the hydrological and sedimentological connectivity between arable land and the kettle hole. A topographic change up to 17 cm (53 yr)⁻¹ in the eroded parts of the catchment is not able to explain the current soil profile truncation that exceeds the ²³⁹⁺²⁴⁰Pu derived topographic change substantially. Hence, tillage erosion already started before the is not limited to the time since the onset of intense mechanisation since the 1960s. In general, the study stresses the urgent need to consider tillage erosion as a major soil degradation process that can be the dominant soil redistribution process in sloped arable landscapes. In general, the study stresses the urgent need to consider tillage erosion as a very important soil degradation process that drives patterns of soil properties in our arable landscapes.

¹Department of Environmental Systems Science, Eidgenössische Technische Hochschule Zürich, Zürich, Switzerland

²Institute for Geography, Universität Augsburg, Augsburg, Germany

³Chemistry and Biochemistry, Northern Arizona University, Flagstaff, USA

⁴Working Group Landscape Pedology, Leibniz-Centre for Agricultural Landscape Research ZALF e.V., Müncheberg, Germany

⁵ Institute of Environmental Science and Geography, University of Potsdam, Potsdam, Germany

1. Introduction

45

Soil erosion is a major threat for the supply of soil related ecosystem services (Montanarella et al., 2016). Over the past decades, particularly the off-site effects associated with water erosion, like nutrient inputs from arable lands into inland waters (Pimentel and Burgess, 2013) or siltation of reservoirs (Krasa et al., 2019), were in the scientific and political focus. Within the European Union, the focus on off-site erosion effects is partly caused by the definition of the goals of the EU Water Framework Directive (EU 2000/60/ES) that focuses mainly on water bodies and floodplains but not on a fully integrated catchment management that would call for complex shared responsibilities between different administrative units. Thereby, other soil erosion drivers than waterlike tillage and wind are somewhat out of the scope of most studies. Tillage erosion is a mostly ignored soil erosion process (Fiener et al., 2018) that, however, substantially contributes to on-site effects on soil properties and hence agricultural productivity (Winnige, 2004; Nie et al., 2019). Van Oost et al. (2006) pointed out that tillage erosion rates are globally at least in the same order of magnitude as water erosion rates. In the Parisian Basin of France, Chartin et al. (2013) demonstrated the dominating role of tillage erosion. Particularly areas of a hilly-hummocky topography with short summit-footslope distances, such as young morainic areas, can be subject to pronounced in-field soil degradation patterns caused by tillage erosion (Winnige, 2004; Deumlich et al., 2017). Young morainic areas that are under intense arable cultivation and corresponding associated tillage erosion are widespread in northern Europe, Canada, northern USA, Russia and eastern Argentina. Measuring or monitoring water and tillage erosion is challenging as both processes are interlinked and correspond to topography are partly strongly controlled by topography (Van Oost et al., 2005b; Van Oost et al., 2006). Water erosion calls for for tThe quantification of water erosion requires a sufficiently long monitoring time (typically decades) to cover a statistically representative variation of rainfall events occurring on different land cover conditions (Fiener et al., 2019). Therefore, thousands of plot experiments, either driven by natural or artificial rainfall simulations, were carried out in different environments and different land cover conditions (Cerdan et al., 2010; Auerswald et al., 2014). Furthermore, a large number of small catchment studies were performed to include quantify both erosion and depositional processes (for overview see; Figure 1 al., 2019). However, soil erosion monitoring is mostly based on sediment delivery outlet monitoring, which cannot address catchment internal redistribution. In contrast, tillage erosion can only be measured based on the movement of beforehand applied tracers or by morphological change monitoring (for an overview of tillage erosion measuring techniques see; Fiener et al., 2018). However, these beforehand applied tracers and change monitoring methods cannot assess the soil redistribution history of sites provide a reconstruction of soil redistribution of the past. Natural or anthropogenic tracers in soils that are inherent to specific soil layer characteristics—can be used to understand the soil redistribution (Fiener et al., 2018). Especially anthropogenic radionuclides (e.g. ¹³⁷Cs, ²³⁹⁺²⁴⁰Pu, ²¹⁰Pb, ⁷Be) have demonstrated their ability to determine changes in topography (Mabit et al., 2014; Alewell et al., 2017; Deumlich et al., 2017). The force of atmospheric n-Nuclear weapon tests lifted transported radioisotopes up to outside the stratosphere troposphere (8 20 km m.a.s.l.; Aguado and Burt, 2015), where circulation mixture led to a n almost (regionally) homogeneous spatial distribution and subsequent corresponding fallout on soils by rainvia precipitation (Meusburger et al., 2016). The main period of atmospheric nuclear weapon tests is from 1953 to

1964 (Schimmack et al., 2001), while the limited Ttest Bban Ttreaty caused a rapid end decrease of atmospheric bomb tests in 1963-1964 (Wallbrink and Murray, 1993; Evrard et al., 2020). This rapid end-decrease leads to a distinct peak in the activity of radioisotopes in soils, which enables the use of radioisotopes as redistribution tracers in soils (Alewell et al., 2017). The radioisotope ¹³⁷Cs has been used as a soil redistribution tracer in a large number of studies (e.g. Porto and Walling, 2012; Chartin et al., 2013; Evrard et al., 2020) and has become a widely used method in soil erosion science. However, the Chernobyl disaster in (1986) supplied additional radioactive fallout to soils across large areas of Europe re contaminated large areas of Europe with 137Cs (Evangeliou et al., 2016). For some years after the Chernobyl disaster, aAn unmixing of the Chernobyl fallout from the original (1960s) bomb peak signal was able-possible by the use of the ¹³⁴Cs/¹³⁷Cs ratio (Lust and Realo, 2012). However, due to the short ¹³⁴Cs half-life of 2 yr (Schimmack et al., 2001), this method cannot be applied anymore. Hence, the use of ¹³⁷Cs as a soil redistribution tracer in Europe is associated with large uncertainties and requires special attention concerning a potential Chernobyl contamination (Evangeliou et al., 2016). Furthermore, due to the ¹³⁷Cs half-life of about 30 yr, decay has already been led to a pronounced reduction (73% in 2020) of the activity until today (Alewell et al., 2017). Over the past decade, ²³⁹⁺²⁴⁰Pu has been discussed and tested as an alternative radioisotopic tracer for soil erosion studies. Decay is not an issue as the half-life of 239 Pu and $^{+240}$ Pu is long (239 Pu = 24000 yr; 240 Pu = 6563 yr.) and the $^{239+240}$ Pu contamination by the Chernobyl accident was spatially very limited (<100 km; Kashparov et al., 2004; Matsunaga and Nagao, 2009) and can be determined by the ²³⁹Pu/²⁴⁰Pu ratio (Alewell et al., 2014; Alewell et al., 2017).

Radionuclide tracers integrate soil erosion processes over time (e.g. since the bomb peak of the 1960s in case of ¹³⁷Cs and ²³⁹⁺²⁴⁰Pu), which somewhat averages out the large temporal variability of water (episodic nature) and tillage (mechanisation) erosion. However, the use of radioisotopiee tracers integrates all kinds-types of soil redistribution processes and lacks insightsdoes not provide information on the relative contribution of the driving processes at play (e.g. water, tillage, wind). Unravelling the respective contributions of these different processes To unravel these different processes calls for requires the use of an inverse modelling approach carrying out model runs of with different parameterisations to alter the contribution and mechanisms of different soil redistribution drivers. There are only few models that take fusing both water and tillage erosion processes into account. Physically oriented models like MCST-C (Wilken et al., 2017b) and LandSoil (Ciampalini et al., 2012) work event based and simulate individual erosion events and are developed for to enhance process understanding, while conceptual USLE based models (WaTEM/SEDEM: Van Oost et al., 2000; Van Rompaey et al., 2001) aim at a robust prediction of long-term soil erosion rates (Alewell et al., 2019). For an inverse modelling approach to unravel tillage and water erosion based on radionuclide tracer, it is necessary to use a parsimonious approach with a limited parameter space covered by and available input data over five to six decades, which suggests the use of conceptual models.

In this study, we will determine the soil redistribution patterns in a small 4.2 ha catchment based on high-resolution ²³⁹⁺²⁴⁰Pu measurements and analyse the contribution of water and tillage erosion processes based on an inverse modelling approach using a combined water and tillage erosion model. The general aim-objective is to unravel the importance of water and tillage erosion driving thefor current variability of soil properties in an intensively used arable landscape of north-eastern Germany.

2. Methods

100

105

110

115

120

125

130

2.1 Study area

The study area (53°21'2 N, 13°39'5 E) is situated in the hummocky ground morainic landscape of the Weichselian glacial belt ('young morainic area') of north-eastern Germany (Fig. 1). Characteristic for these landscapes are widespread closed depressions, so-called kettle holes, which result from a delayed melting of dead ice blocks. They are nowadays filled with mineral soil, (degraded) peat or water. The study area is part of a kettle hole catchment (4.2 ha; Fig. 1) and consists of different showing a high topographical morphological variability covering convex hilltops, steep slopes and flat areas locations. The recent crop rotation is rape (Brassica napus L.)-winter wheat (Triticum aestivum L.)-winter barley (Hordeum vulgare L.)winter barley, cultivated without cover crops, which is a typical conventional crop rotation that is adapted for the highly fertile soils of the Uckermark region. The mean arable land of a farm in the region is 352 ha, which is much larger compared to the mean of the State of Brandenburg (250 ha) and Germany (60 ha; Troegel and Schulz, 2018). These larger field sizes are explained by mainly caused by land consolidation programmes implemented in the 1960s during the socialist period. However, also before, agriculture in the region was already characterised by large scale farming structures (East Germany in 1939: 44%) of farms manage more than 5 ha of agricultural land; Wolz, 2013) and corresponding high agricultural mechanisation. In 1939, large farms that manage more than 100 ha of arable land cultivated 7% of the total arable area of Germany. In contrast, within the present-day federal states of Mecklenburg-Pomerania, Brandenburg (study area location) and Saxony-Anhalt, large farms cultivated 30% of corresponding arable land (Wolz, 2013). The catchment is part of a single large field (54 ha), which is a size that can be frequently found in the region. The soils are developed from glacial till and vary with respect to their location in the landscape. Convex hilltops and steep slopes are dominated by extremely eroded A-C profiles (Calcaric Regosols, soil classification according to: IUSS, 2015), while Luvisols showing different degrees of erosion and that are typically situated at the up and mid slopes, the footslopes and depressions show a sequence of Glevic Colluvic Regosols, Mollic Glevsols and (buried) Terric Histosols are dominated by Glevic-Colluvic Regosols (Fig. 1b; Sommer et al., 2008; Gerke et al., 2010). These soils regularly reveal fossil surface horizons below 1 m depth (fAh, fH). The closed kettle hole depression itself is built up by degraded Histosols and covered by a thin colluvial layer of mineral soil (40±8 cm mean, 25% and 75% quantile, n = -20; based on soil auger prospection). The study area has a continental climate (Köppen: Dfb) with low annual precipitation (500 mm; Fiener et al., 2018) and high temperature amplitude (Jul = $\div 18^{\circ}$ C, Jan = $\div -0^{\circ}$ C; mean 8.9°C WMO-CLINO 1981-2010 for the meteorological stations Gruenow and Angermuende). Between 7 and 11 erosive rainfall events per year take place each year (Deumlich, 1999). In the region, maximum intensities up to 162 mm h⁻¹ (10-min interval) were recorded during an extreme event in 2016 (Wilken et al., 2018).

2.2 Soil sampling design and preparation

The soil sampling design was organised <u>according toin</u> a regular 20 m x 20 m grid with at least one sampling point<u>of the transect line</u> exceeding the spatial extent of the catchment under study (Fig. 1) to avoid boundary effects. To assess small scale

spatial variability (for distances of sampling points between 5 m and 20 m) a nested sampling approach was applied (Fig. 1; Hengl and MacMillan, 2019). Therefore, five densified sub-grids, located at different topographical locations (hilltop, ridge shoulder, moderately steep mid slope, steep mid slope, foot slope/valley; Fig. 1) were selected. In total, 209 locations were included in the sampling design.

The sampling points were located using a differential GPS (AgGPSTM 132; Trimble Navigation Ltd, Sunnyvale CA, USA) applying the SAPOS (LGB) correction signal. With respect to drill penetrability, soil sampling was carried out under moderately wet soil moisture conditions (ranginge from 18% to 32% and 16% to 33% for topsoil and subsoil, respectively) in December 2015. Closed soil cores, using a steel drill containing a plastic liner (4.6 cm inner diameter), were driven by a percussion corer (Cobra TTe; Atlas Copco Power Techniques GmbH, Stockholm, Sweden) into the ground. Soil cores driven down to a depth of 50 cm-were taken at all-209 sampling points. To account for the vertical distribution of ²³⁹⁺²⁴⁰Pu in the soil profile, ten replicate soil cores were taken at five up hill and five foot slope locations (Fig. 1; P1 P10). Thus, overall 219 soil cores at 209 locations were taken (Fig. 1).

To minimize physical and biogeochemical disturbance, the soil cores were stored in a freezer until sample preparation. After complete thawing, the soil cores were separated into topsoil (Ap horizon) and subsoil. The separation was done by visual interpretation of soil horizon characteristics (colour, structural and density differences), showing a variation in topsoil thickness between 16 and 30 cm (mean of 23.5 cm) depending on the topographic position. Aliquot ($n=\div_3$) samples for each topsoil and subsoil location were taken for gravimetric water content (weighted before and after drying at 105° C) and dry bulk density (known sample volume) measurements. The soil samples were air dried and subsequently sieved with a 2 mm mesh to separate stones from the fine soil.

2.3 ²³⁹⁺²⁴⁰Pu measurements

135

140

145

150

155

160

All topsoil samples ($n = \div 209$) were analysed, while 145 (~70 %) of the subsoil samples of highest topsoil activities were measured on their $^{239+240}$ Pu activity. This was done to reduce the <u>inventory number</u> of samples <u>that havewith</u> Pu activities below the detection limit. Furthermore, at 10 locations high<u>er</u>-resolution (5 cm) depth increments were measured to assess the depth distribution of $^{239+240}$ Pu activity below the mixed plough layer.

The fallout radionuclides ²³⁹⁺²⁴⁰Pu were used to estimate effective soil redistribution since the 1960s. Plutonium isotopes measurements were conducted following Calitri et al. (2019) based on the procedure of Ketterer et al. (2004). Before the mass spectrometry analysis, 10 g of milled fine earth were dry-ashed for at least 8 hours at 600°C to remove organic matter. Subsequently, the samples were spiked using 30 pg (c. 0.0044 Bq) of a ²⁴²Pu tracer solution (NIST 4334). The sample leaching was applied using 16 M nitric acid (HNO₃) overnight at 80°C and subsequently filtered and adjusted to a concentration of 8 M HNO₃. Plutonium species were adjusted to the Pu (IV) oxidation state using first an acidified FeSO₄·7H₂O solution (2 mg ml⁻¹ of leached solution) and subsequently a sodium nitrite (NaNO₂) solution (20 mg ml⁻¹ of leached solution). The samples were heated at 75°C for two hours. Tetravalent Pu was separated from the leached solution using a Pu-selective TEVA resin (2 mg of TEVA per millilitre of leached solution). Following occasional agitation for two hours, the resin was collected in a

pipette tip equipped with a glass_wool plug. This disposable column was rinsed with 2 M aqueous HNO₃ to remove unretained matrix elements [e.g. uranium (U)], then rinsed with 8 M HCl to elute thorium (Th) and finally rinsed again with 2 M aqueous HNO₃ (rinse volume = ÷1 ml per 30 mg of TEVA). Plutonium was eluted using 0.05 M aqueous ammonium oxalate. Data quality was evaluated through the analysis of blanks (soils or rocks devoid of Pu), duplicates and control samples of known ²³⁹⁺²⁴⁰Pu activities (Standard Reference material 4350b – River sediment for radioactivity measurements from NIST). Activities of ²³⁹⁺²⁴⁰Pu were measured using a Thermo X Series II quadrupole ICPMS, located at Northern Arizona University. The ICPMS instrument is equipped with an APEX HF high-efficiency sample introduction system. The masses of ²³⁹Pu and ²⁴⁰Pu in the samples were converted into the summed activity ²³⁹⁺²⁴⁰Pu.

2.4 ²³⁹⁺²⁴⁰Pu based soil erosion assessment

180

185

We applied the proportional conversion approach of Walling et al. (2011). Erosion is calculated following equations 1 and 2:

$$SL_i = 10 * BD_i * TD_i * RR_i * T^{-1}$$
 (1)

where SL_i is the mean annual soil loss in Mg ha⁻¹ yr⁻¹, BD_i is the soil bulk density in kg m⁻³, TD_i is the vertical depth of the Ap horizon in m (tillage depth), RR_i is the relative reduction of the reference inventory of the ²³⁹⁺²⁴⁰Pu inventory and T is the years that are elapsed since the end of atmospheric nuclear weapon tests (mainly since 1964).

$$RR_i = \frac{(Pu_{ref} - Pu_i)}{Pu_{ref}} \tag{2}$$

where Pu_i is the inventory at sampling point i and Pu_{ref} is the reference inventory of undisturbed sites in Bq m⁻² (see implementation section 2.5).

For a three-dimensional representation of the $^{239+240}$ Pu redistribution by water and tillage erosion, SPEROS-Pu was developed that is based on a modified version of the SPEROS-C model (Van Oost et al., 2005a; Fiener et al., 2015; Nadeu et al., 2015). We utilized the water and tillage erosion modules of the SPEROS model that are based on WaTEM/SEDEM (Van Oost et al., 2000; Van Rompaey et al., 2001). SPEROS-Pu is a spatially explicit water and tillage erosion model. Water erosion is simulated based on a gridded application of the Revised Universal Soil Loss Equation (RUSLE: Renard et al., 1996) coupled with a sediment transport and deposition approach. Erosion is calculated according to a slightly modified RUSLE approach, transport and deposition is based on the grid cell specific local transport capacity TC (kg m⁻¹ yr⁻¹), which multiplies RUSLE factors with a transport capacity coefficient (k_{to} ; in m)

$$TC = k_{tc} * R * C * K * L * S * P$$

$$\tag{3}$$

where R, C, K, L, S and P are the RUSLE factors (see Renard et al., 1996).

The tillage erosion module of SPEROS-<u>Pu</u>C follows a diffusion-type equation adopted from Govers et al. (1994) that derives tillage erosion based on change in topography and management specific coefficients

$$Q_{til} = -k_{til} \frac{\Delta h}{\Delta x} \tag{4}$$

where Q_{til} is the soil flux in kg m⁻² yr⁻¹, Δh is the elevation difference in m, Δx is the horizontal distance in m while k_{til} is the tillage transport coefficient in kg m⁻¹ yr⁻¹

$$k_{til} = BD_i * TD_i * x_{til} \tag{5}$$

where x_{til} is the tillage translocation distance in m (for BD_i and TD_i see description of eq. 1).

The representation of the ²³⁹⁺²⁴⁰Pu redistribution in the SPEROS-Pu model is three dimensional and accounts for ²³⁹⁺²⁴⁰Pu source area depletion and corresponding redistribution of depleted sediments. The horizontal distribution of ²³⁹⁺²⁴⁰Pu is grid based, while the vertical distribution is represented by ten 10_±-cm depth layers. The two uppermost layers are assumed to be homogeneously mixed by tillage operations and have the same-average ²³⁹⁺²⁴⁰Pu activity of the upper two soil layers. At the beginning of the simulation, the ²³⁹⁺²⁴⁰Pu reference activity is homogeneously distributed within the mixed plough layer and over the entire catchment. Subsequently, the local ²³⁹⁺²⁴⁰Pu inventory is altered by soil redistribution processes. Soil erosion processes lead to a reduction of the ²³⁹⁺²⁴⁰Pu inventory per m² due to-a soil and corresponding associated ²³⁹⁺²⁴⁰Pu loss, which causes and mixing in of non-contaminated subsoil. Deposition adds contaminated material on top and increases the ²³⁹⁺²⁴⁰Pu inventory.

2.5 Implementation and inverse modelling

200

210

215

Soil redistribution based on ²³⁹⁺²⁴⁰Pu measurements

Spatially distributed top<u>soil</u> and subsoil bulk density and tillage depth information for each individual sampling location were

was applied to the proportional conversion approach. The reference inventory of undisturbed sites follows the value determined
by Calitri et al. (2019) who found a ²³⁹⁺²⁴⁰Pu inventory of 43±3 Bq m² based on four sites that did not show profile
morphological or geochemical indication for soil redistribution at a location 8.5 km apart from the study area. To account
address for the uncertainty inherent to the reference measurements determined in close proximity but not at site, a reference
range from 40 to 46 Bq m² was accounted for in the simulations.

The point data of the ²³⁹⁺²⁴⁰Pu inventory for the depth 0-50 cm was geostatistically (block kriging) interpolated for a gridded spatial representation that matches the spatial resolution of the soil redistribution model (5 m x 5 m). Block kriging was used to reduce small-scale scattering that is naturally inherent to soil cores of 4.6 cm diameter that are supposed to represent a decametre scale. Different block sizes were tested <u>forin</u> the kriging approach. A block size of and finally 20 m was selected that matches the sampling resolution and has shown did not to lead cause in over-smoothening of the interpolation result. The theoretical semivariogram model (Fig. 2) was fitted using all 209 sampling points, including the nested samples to account for variations over short distances. However, the input data of the interpolation itself solely uses the regular 20 m x 20 m grid points. The interpolation and geostatistical analysis were carried out using the statistical software GNU R (R-Core-Team, 2015), version 3.5.3 and the add-on package gstat (Pebesma, 2004).

Inverse modelling of water and tillage erosion

An inverse modelling approach was used to understand the proportion of water and tillage erosion that is inherent to the ²³⁹⁺²⁴⁰Pu based soil erosion map. The inverse modelling iterates three parameter sets from low to extreme settings over the 53 yr-modelling period (1964-2016): (i) the k_{til} tillage translocation coefficient (as given for illustration in Eq. 5), (ii) the product of all RUSLE factors (as given in Eq. 3; in the following referred to water erosion strength) and (iii) the water erosion transport capacity coefficient k_{tc} (see Table 1) that controls the transport distance and is the standard calibration parameter of the model.

While changes of the tillage translocation coefficient and water erosion strength only alter the quantity of soil redistribution, the k_{tc} has a pronounced impact on spatial patterns of modelled soil redistribution. The parameter range covers very low to extreme soil redistribution rates (k_{til} max= 1000 kg m⁻¹; k_{tc} max= 500 m; RUSLE-factors product deviation = 100%; see Table 1). The water erosion reference parameterisation for k_{tc} is 150 m (Van Oost et al., 2003). The interplay of parameter combinations was assessed in 35722 different model runs (Table 1).

To determine the model match, different goodness_-of_-fit parameters were calculated that compare the interpolated ²³⁹⁺²⁴⁰Pu raster map against the results of the raster results calculated by the inverse modelling approach. To address the high spatial variability of the 5_m x 5 m raster by raster comparison, a classification of results was carried out. Therefore, mean values were calculated based on the cells that fall into a specific class of the interpolated map of ²³⁹⁺²⁴⁰Pu inventories. The classification covers 20 classes with 2.5 Bq m⁻² steps from 17.5 to 65 (and a class >65) Bq m⁻² of ²³⁹⁺²⁴⁰Pu. First, the spatial correlation was calculated for both the raster by raster comparison and the classified results. Second, the classified results of the inverse modelling were tested using goodness_-of_-fit parameters that take absolute differences between observed and predicted values into account (RMSE, model efficiency coefficient: MEF according to Nash and Sutcliffe, 1970). As a last step, the results of the measured and modelled ²³⁹⁺²⁴⁰Pu inventories were transferred into tillage and water erosion maps (given in Mg ha⁻¹ and topographical change in cm) applying the proportional conversion approach (see chapter-2.4²³⁹⁺²⁴⁰Pu based soil erosion assessment).

3 Results

230

235

240

245

3.1 ²³⁹⁺²⁴⁰Pu activities and inventories

The topsoil and subsoil ²³⁹⁺²⁴⁰Pu activities differ substantially from each other and show distinct spatial patterns according to their topographic position. All topsoil samples (n=+209) showed a ²³⁹⁺²⁴⁰Pu activity above the detection limit, while 7 of the 145 subsoil samples fall below the detection limit (< 0.002 Bq kg⁻¹). Those 7 samples are all located at positions with ²³⁹⁺²⁴⁰Pu inventories below the lower reference boundary (40 Bq m⁻²). The average ²³⁹⁺²⁴⁰Pu activity is 0.078 ± 0.016 Bq kg⁻¹ and 0.035±0.038 Bq kg⁻¹ for topsoil and subsoil, respectively. All The high-resolution depth profiles (5 cm increments) at erosional sites distinctively show a sharp reduction of the ²³⁹⁺²⁴⁰Pu activity below the plough layer at erosional sites (Fig. 3). In turn, while depositional sites show more complex depth distributions. Location P4 (Fig. 3) does not show a drop in activity until a

250 depth of 0.5 m, while P1 (and partly P3) shows an increase of the ²³⁹⁺²⁴⁰Pu activity with depth that is potentially goes back to the caused by Pu enrichment processes during lateral transport or the deposition of already Pu depleted source material into the topsoil. The topsoil ²³⁹⁺²⁴⁰Pu/reference (43 Bg m⁻²) ratio indicates soil erosion related ²³⁹⁺²⁴⁰Pu depletion or enrichment according to a ratio lower and higher than one, respectively. The highest depletion (min = $\div 0.28$; 5% quantile = $\div 0.37$) can be found at the hilltops that are most affected by tillage, while enrichment (max = 1.18; 95% quantile = 0.92) is spatially limited 255 to the flat surroundings of the kettle hole (Fig. 1), where topsoil material was potentially deposited by both water and tillage soil redistribution processes. At 14 (of 209) sampling locations, a higher subsoil than topsoil ²³⁹⁺²⁴⁰Pu activity was found. which points at deposition of ²³⁹⁺²⁴⁰Pu depleted sediments. The majority of these locations show enriched ²³⁹⁺²⁴⁰Pu activities in the subsoil (119 of 14), that goes in line with higher subsoil activities compared to the topsoil (13 of 14), which is caused by deposition of ²³⁹⁺²⁴⁰Pu depleted sediments. These locations are all, except for one, located at the kettle hole surrounding plateau where both water and tillage erosion show cause deposition. The ²³⁹⁺²⁴⁰Pu depletion of sampling points (including 260 locations outside the study catchment) goes down to 12 Bq m⁻² while the highest five locations exceed 86 Bq m⁻², which means that the ²³⁹⁺²⁴⁰Pu inventory has more than doubled compared to the reference inventory of 43 Bg m⁻² and therefore a tillage depth of 25 cm, which has to be attributed to enrichment processes. Therefore, these As the enrichment processes inherent to these -five locations cannot be corrected, the locations were excluded from the analysis.

The distribution of the interpolated maps covering the study catchment shows that substantially more locations fall below the reference inventory than exceeding it (Fig. 4). This indicates that a larger area is subject to erosion processes compared to depositional processes.

3.2 ²³⁹⁺²⁴⁰Pu measurements vs. inverse water and tillage erosion modelling

280

that was qualitatively quantitatively analysed by goodness_-of_-fit parameters. The spatial correlation between the ²³⁹⁺²⁴⁰Pu derived patterns and the modelled best knowledge soil erosion_redistribution, including both water and tillage erosion, is only moderate (R²÷=0.45, Rho = 0.73) on a raster by raster comparison (n÷=1699, 5 m x 5 m grid points; Fig. 5a). This is not surprising due to short term and small scale topographic dynamics (e.g. roughness, wheel tracks, vegetation artefacts) that transfer into model results as a static digital elevation model is used. To reduce this-small-scale variability and understand the average goodness_-of_-fit, the inverse modelling results were classified according to the measured ²³⁹⁺²⁴⁰Pu activity. The classified results average out the spatio-temporal dynamics and show a very high correlation (R²÷=0.95, Rho=÷0.99; Fig. 5b), which pinpoints_illustrates the great agreement of the spatial soil redistribution patterns between the ²³⁹⁺²⁴⁰Pu measurements and the model results.

While the analysis of the spatial correlation is a relative comparison, the absolute deviation is taken into account considered according to the MEF (model efficiency coefficient; Nash and Sutcliffe, 1970; 1 = perfect prediction, 0 = as good as mean of all measurements, < 0 = worse than mean). The quality of model predictions shows hardly any sensitivity to water erosion related parameterisations (k_{tc} and erosion strength; Figure 6c). In contrast, the tillage erosion strength, represented by k_{til}

parameter iterations, showed a substantial impact on the MEF (Fig. 6a & b). A MEF better than 0.8 and RMSE below 6.5 Bq m⁻² were found for a k_{til} range from 225 to 475 kg m⁻¹, while T the best model fit was found for a k_{til} of 350 kg m⁻¹ achieving a MEF of 0.87 and, while the a corresponding RMSE of 5.2 Bq m⁻². The best model fit was found without the contribution of water erosion. The highest impact on the best-fit model run was a 0.31 MEF-reduction by an extreme water erosion parameterisation ($k_{tc} = 500$, water erosion strength = 200%).

Soil redistribution determined by the proportional conversion approach using ²³⁹⁺²⁴⁰Pu measurements, indicates substantial morphodynamics-geomorphological dynamics in the study catchment over the past decades. Soil erosion at hilltop locations is shown to be-reach up to 14.9 cm (43 Bq m⁻² reference; 40 Bq m⁻² reference = 14.1 cm; 46 Bq m⁻² reference; = 15.6 cm), while deposition partly can builds a colluvium layer up-with a maximum thickness of 21.5 cm (43 Bq m⁻² reference; 40 Bq m⁻² reference = 24.9 cm; 46 Bq m⁻² reference = 18.6 cm)_colluvium_over the past 53 yr. The inverse modelling stresses that substantial soil erosion, which takes place over large areas, is almost exclusively attributed to tillage translocation (modelled max. water erosion = 3.8 cm (53 yr)⁻¹ vs. max. tillage erosion = 13.5 cm (53 yr)⁻¹; Fig. 7c, d). In turn, both processes contribute to deposition in the kettle hole surrounding flats (max. water deposition = 27.1 cm (53 yr)⁻¹ vs. max. tillage deposition = 22.4 cm (53 yr)⁻¹; Fig. 7c, d).

4 Discussions

285

290

300

305

310

4.1 ²³⁹⁺²⁴⁰Pu methodological benefits and limitations

The use of fallout radionuclides to determine soil redistribution patterns and rates over the past decades has been used in many studies in various study areas around the world (see reviews: Mabit et al., 2014; Alewell et al., 2017; Evrard et al., 2020) and contributed substantially to understand soil degradation processes. However, the most frequently used fallout radionuclide ¹³⁷Cs faces upcoming limitations (Chernobyl fallout that adds on the global fallout over large parts of Europe and ongoing decay below detection limit of standard measuring devices; also see section 1) in the use as a soil redistribution tracer (Evrard et al., 2020). The fallout radionuclide ²³⁹⁺²⁴⁰Pu has demonstrated its suitability to determine the recent soil redistribution history (since the 1960s; see review Alewell et al., 2017) and is a potential alternative for fills the gap of upcoming limitations in the use of ¹³⁷Cs as a soil redistribution tracer_(Mabit et al., 2013; Alewell et al., 2017). In Europe, where large parts were recontaminated by ¹³⁷Cs fallout of the Chernobyl accident (Evangeliou et al., 2016), additional information on the spatial change on the inventory is needed to derive accurate soil redistribution rates. Particularly in the area of the former GDR, almost no information that can be used for a correction on the ¹³⁷Cs Chernobyl re-contamination are available (Evangeliou et al., 2016). The ²³⁹⁺²⁴⁰Pu fallout caused by the Chernobyl disaster was very local (radius <100 km) and has a distinct fingerprint based on the ²³⁹Pu/²⁴⁰Pu ratio. While the ²⁴⁰Pu/²³⁹Pu ratio of global fallout in the Northern Hemisphere is 0.180±0.014 (Kelley et al., 1999), the ²⁴⁰Pu/²³⁹Pu ratio soils that received high Chernobyl fallout is about twice as high (0.408±0.003, determined for soils within the 30 km exclusion zone of the Chernobyl reactor; Muramatsu et al., 2000; Boulyga and Becker, 2002). The 95% interval of confidence and average of the ²⁴⁰Pu/²³⁹Pu ratio found in the soil samples of this study were 0.281 and 0.199, respectively. Hence, a relevant ²³⁹⁺²⁴⁰Pu re-contamination by Chernobyl fallout can be ruled out for the study area. Another limitation for the use of ¹³⁷Cs as a soil redistribution tracer is the ongoing decay due to short half-life times that has already caused a substantial reduction of the inventory. Due to lower activities, measuring devices of much higher complexity are needed in the future (Evrard et al., 2020). Decay is not an issue for ²³⁹Pu and ²⁴⁰Pu as both nuclides have long half-life times that allow for a quasi-unlimited use, however, it needs to be mentioned that sample preparation for ²³⁹⁺²⁴⁰Pu ICP-MS
 measurements is much more laborious compared to the standard procedure of physical ¹³⁷Cs measurements. However, some methodological limitations persist that need to be taken into account.

325

330

335

340

Enrichment processes, due to selective transport of soil constituents that fallout radionuclides are preferentially associated with, are a critical issue for the use of most (e.g., ²³⁹⁺²⁴⁰Pu, ¹³⁷Cs, ²¹⁰Pb) radionuclide tracers (Parsons and Foster, 2011; Mabit et al., 2014; Alewell et al., 2017). While ¹³⁷Cs is mainly associated with clay particles, ²³⁹⁺²⁴⁰Pu binds to soil organic matter and oxides (Alewell et al., 2017) that are less affected by selective water transport and corresponding ²³⁹⁺²⁴⁰Pu enrichment (Meusburger et al., 2016; Xu et al., 2017). However, it needs to be mentioned that radionuclide associated particles are typically not transported as primary particles but in soil aggregate complexes (Hu and Kuhn, 2014; Hu et al., 2016), which has a pronounced effect on enrichment processes (Wilken et al., 2017b). Nevertheless, the ²³⁹⁺²⁴⁰Pu activity at depositional sites, that are redistributed by water (transport by tillage is typically assumed to be non-grain size selective; Fiener et al., 2018), can be higher in relation to the activity of the source material. A soil profile that shows a distinct indicator of enrichment processes in this study is sampling profile P1 (25-45 cm; Fig. 3) that is situated in the kettle hole surrounding flat. Hence, enrichment in fine particles of relatively high ²³⁹⁺²⁴⁰Pu activity is to some extent also an issue within this study that causes an overestimation of deposition. A particle size correction factor was not applied as topsoil enrichment (topsoil Bq m⁻² > ref. 43 Bq m⁻²) was exclusively found at very few sampling locations (<6%) in the kettle hole surrounding flats. Furthermore, the mean topsoil ratio of enriched sediments is moderate (1.2) and supports the general assumption that ²³⁹⁺²⁴⁰Pu is less affected by selective transport compared to ¹³⁷Cs (Alewell et al., 2017) and that transport by tillage is non-grain size specific. The counteracting process of enrichment is the deposition of ²³⁹⁺²⁴⁰Pu depleted sediments that are transported from highly eroded locations. Such highly depleted locations can be found at the hilltops of the study area (Fig. 7b). Hence, the hilltops are the main source of highly depleted sediments that are deposited in kettle hole surrounding flats. However, the minimum horizontal distance from the hilltops to the kettle hole surrounding flat is roughly about 70 m and the approximate tillage translocation distance 0.5 to 1 m per pass (Fiener et al., 2018). Hence, deposition of depleted ²³⁹⁺²⁴⁰Pu material has to be mainly attributed to surface runoff that can bridge-flow across longer transport distances. SPEROS-Pu takes depletion of deposited sediments into account but does not address enrichment processes. Furthermore, a maximum soil sampling depth down to 50 cm was carried out within this study that technically allows to derive a maximum depositional depth of 25 cm using the proportional conversion approach of Walling et al. (2011), which is at four sampling locations exceeded was exceeded at four sampling locations. Nevertheless, also with a deeper soil sampling, it would be arguable if these potentially enriched or depleted sampling locations should be excluded from the statistical analysis, like it was done for extreme depositional locations (4 sampling locations) within this study.

The application of soil tracers like fallout radionuclides are based on the assumption that spatial and vertical patterns are exclusively caused by soil redistribution processes due to water and tillage erosion. Bioturbation or colloid migration can be drivers of vertical displacement, which can cause an incomplete representation of the inventory if the downward migration exceeds the soil sampling depth. Within this study, a rapid reduction of the ²³⁹⁺²⁴⁰Pu activity was found below the plough and colluvial layer of the high resolution depth profiles (see Fig. 3). Hence, there is no indication for a pronounced downward migration of ²³⁹⁺²⁴⁰Pu below the sampling depth.

4.2 Using ²³⁹⁺²⁴⁰Pu and inverse modelling to understand the recent soil erosion history

350

355

360

365

370

375

380

Within this study, an inverse modelling approach was carried out to understand the contribution of soil redistribution by water and tillage erosion. The model is subject to specific uncertainties that need to be mentioned. The diffusion type equation for the tillage erosion simulation (Govers et al., 1994) follows the assumption of a spatially homogenous tillage translocation coefficient for the entire study catchment. However, as the tillage translocation coefficient is a function of tillage speed and depth, tillage translocation distances are likely to show spatial differences that may follow the topography of the study area. Furthermore, the model uses a static digital elevation model that does not account for topographical change during the simulation period, which causes static soil redistribution patterns that ignore feedback processes. This is an issue for the used digital elevation model that represents short-term topographical structures like agricultural tramlines at the acquisition time. To reduce this effect, a low pass filter was applied on the digital elevation model to somewhat even out short-term structures. Numerical dispersion, can affect the model results, which is related to the vertical and spatial representation of the model. The vertical soil profile representation in 10 cm increments is rather low for a fallout radionuclide tracer with a rapid decrease of ²³⁹⁺²⁴⁰Pu between the plough layer/colluvium and the subsoil layer (see Fig. 3). However, the calculation of soil redistribution is based on relative changes of the ²³⁹⁺²⁴⁰Pu inventory in relation to reference inventories. Therefore, the sensitivity of the soil redistribution calculations on the ²³⁹⁺²⁴⁰Pu soil profile development is minor as the ²³⁹⁺²⁴⁰Pu inventory is independent from the depth distribution. The relatively high spatial resolution of 5 m x 5 m was selected to adequately represent the high landscape variability in the study area and has reliably simulated spatial patterns in previous studies (e.g. Van Oost et al., 2003; Dlugoß et al., 2012). Overall, the model performs well and explains 95% of the variance and achieves a MEF better than 0.8 in predicting ²³⁹⁺²⁴⁰Pu patterns by simulating the combined effect of three model parameters (tillage translocation coefficient, water transport capacity coefficient, water erosion strength).

Within the intensively <u>used managed</u> study catchment, substantial ²³⁹⁺²⁴⁰Pu derived soil redistribution was found with soil loss up to 45 Mg ha⁻¹ yr⁻¹ (ref. 43 Bq m⁻²; ref. 40 and 46 Bq m⁻² = 43 and 47 Mg ha⁻¹ yr⁻¹) and sediment deposition up to 65 Mg ha⁻¹ yr⁻¹ (ref. 43 Bq m⁻²; ref. 40 and 46 Bq m⁻² = 75 and 56 Mg ha⁻¹ yr⁻¹). Very high deposition can only be found in the spatially narrow area of the kettle hole surrounding flat where both <u>water and tillage erosion</u> processes <u>water and tillage erosion</u> lead to deposition (Fig. 1). The kettle hole surrounding flat is a spatially narrow area, but the only <u>region zone</u> where water erosion substantially contributes to pronounced <u>morphodynamics geomorphological dynamics</u> (Fig. 7d). As a result of the small spatial <u>contribution extent</u> where this process takes place, the inverse modelling shows hardly any sensitivity on

goodness—of—fit changes in reaction to the variation in model parameterisations (Fig. 6c). Nevertheless, sediment deposition and delivery by surface runoff is an relevant important process in the study area. Evidence for runoff based runoff-based sediment delivery is a colluvial layer covering the peat in the kettle hole with an average depth of 40 cm. This sediment delivery into the kettle hole cannot be explained by the inverse modelling of water erosion applying a reasonable parameter range-of the inverse modelling. Hence Therefore, we assume the reference parameterisation for the region given by the state of Brandenburg of the region needs to be assumed as the most appropriate (k_{tc} $\not\leftarrow$ 150 m and RUSLE parameters according to Tab. 1). According to the model run using the reference parameterisation for water erosion, a colluvial layer of 1.7 cm (53 yr)⁻¹ would have been developed on top of the peat that has been exported from the arable part of the catchment (see Fig. 1) due to water transport over the past decades. This indicates a long water erosion history before the 1960s. This is not surprising as bare soil conditions and erosive rainfall events have taken place since the onset of arable use approxapproximately, 1 k-yr. before present (Van der Meij et al., 2017; Kappler et al., 2018). In turncontrast, tillage erosion is typically assumed to be a process that is linked to recent developments of increasing mechanical forces that are have been applied to soils over the past century (Sommer et al., 2008; Calitri et al., 2019). Within this study, a maximum topographical change by hilltop erosion up to 17 cm (53 yr)-1 was determined. In a review on tillage erosion by Van Oost and Govers (2006), tillage translocation coefficients of 44 experiments were reported for different tillage practices. This resulted in a mean k_{ril} a mean: of 234 kg m⁻¹ (; 5% percentile = 30 kg m⁻¹; 95% percentile = 640 kg m⁻¹) for mouldboard and chisel plough. Within this study, a tillage translocation coefficient of 350 kg m⁻¹ per year was determined. The tillage translocation coefficients, determined by the inverse modelling approach, are rather high compared to other studies considering that fallout radioisotopic tracer approaches integrate cover a phase of high mechanical development from low to high power farming machines (Sommer et al., 2008; Keller et al., 2019). Although recent tillage translocation rates are rather high they cannot explain the soil depth patterns that are visible by augerings. In the study region, it can be observed that tillage erosion mainly affected hilltops. Calcaric glacial till is approaching the surface by soil profile truncation and is partially mixed into the plough layer. Within the study catchment, this is the case for 20 sampling locations ($CaCO_3 > 0.5\%$) that are also indicated as strongest-the most eroded sites by the $^{239+240}$ Pu measurements and the inverse modelling. Non-eroded reference profiles (n= \div 210) in the region show the parent material (calcaric glacial till) is found at 102 cm depth on average (van der Meij et al., 2019). Hence, less than 17% of soil depth reduction can be attributed to most recent process dynamics. This suggests that traditional hand or cattle based tillage systems, which are used since the beginning of arable agriculture in the region (1k yr BP; Kappler et al., 2018), must have caused severeextensive soil redistribution in theover long runperiods. This suggests that tillage erosion might be the dominant process even without mechanized soil tillage, which is the common practice in most developing countries that also partly cultivate very steep slopes. Therefore, the general assumption of tillage erosion being only an issue for highly mechanised agricultural systems (Van Oost et al., 2006) might need to be re-evaluated reconsidered across a range of contrasted agricultural environments.

390

395

400

405

4.3 Interplay of sediment redistribution by water and tillage

415 The inverse modelling has shown that soil redistribution by water has only a minor impact on erosion processes in the study area. However, sediment deposition by water has a complex interplay with tillage translocation (kettle hole surrounding flat; Fig. 7). Very high deposition by tillage translocation towards the field-kettle hole edge (typically >1 m known from soil augering; Kappler et al., 2018) builds up local hydrological depressions (Fig. 1 & 7). Only large and rareinfrequent extreme events exceed the critical runoff quantity to connect the arable hillslopes with the inner peat area of enter the kettle hole (Fig. 420 1), while the majority of events force lead to deposition of sediments in the kettle hole surrounding flats (see Fig. 7d; Fig. 3, P1 and P4). Therefore, these catchments show a very limited hydrological and sedimentological connectivity between the arable land and kettle holes. This statement is supported by Ssurface runoff and sediment delivery monitoring in the study catchment (2015-2019) have that has demonstrated that only very few rainfall events produced sufficient runoff to exceed the retention capacity of the kettle hole surrounding flats and caused runoff and associated sediment delivery into the kettle hole (data not shown). Therefore, the study catchment shows a very limited hydrological and sedimentological connectivity between 425 the cultivated area and kettle hole. Hence, tillage translocation in hummocky young morainic regions does also have a pronounced impact on hydrology and biogeochemistry.

4.4 Relevance of tillage erosion and scientific attention

430

440

Our results clearly indicate that soil erosion in the study area is highexceeds the tolerable soil loss rates (according to Schwertmann et al., 1990 = 6 Mg ha-1 yr-1 in the study region) and is mainly attributed to tillage erosion (Fig. 6 & 7). During the socialist era (1949-1990), efficient-productivist agricultural management strategies were implemented that included land reformation consolidation to merge large fields and the use of heavy farming machines (Forstner and Isermeyer, 2000; Wolz, 2013). For instance, annual ploughing was combined with a recommended practice of episodically using a paraplough (tillage depth ~0.6 m; Fachbereichsstandard-DDR, 1985) to break the plough pan. The average field size in the region (Quillow catchment = 22 ha) still consists of large field sizes is rather large, this that has established favoured conventional big farming structures that utilises that is based on powerful machinery. However, tillage erosion does not receive reasonable scientific attention (Fiener et al., 2018), even if the its effects on yields (Oettl et al., 2020), nutrient and carbon cycling (Wilken et al., 2017a; Zhao et al., 2018; Nie et al., 2019) and soil hydrology (Herbrich et al., 2017) are widely known. Globally, tillage erosion has been recognized as an environmental threat in the wide spread hummocky young morainic regions that have shallow soils that are subject to dropping yields at hilltop locations of Canada: , North America , Russia and Northern Europe (Canada: Pennock, 2003; Tiessen et al., 2007a; Tiessen et al., 2007b, North America: Li et al., 2007, 2008, Russia: Olson et al., 2002; Belyaev et al., 2005 and Northern Europe: Quine et al., 1994; Heckrath et al., 2005; Wysocka-Czubaszek and Czubaszek, 2014) that have shallow soils that are subject to dropping yields at hilltop locations. Most arable regions are subject to pronounced tillage erosion (e.g., illustrated in the landscape by tillage banks along downslope field borders (e.g. illustrated in the landscape by tillage banks along downslope field borders; Chartin et al., 2013), but may not show a pronounced impact on yields (Lal et al., 2000). For instance, IL oess derived soils with a homogeneous grain size distribution for several meters of depth do not show major differences in soil structure (Blume et al., 2016), while nutrient losses are compensated by fertilizer applications. Another reason for not being a prominent soil degradation mechanism might be that the impacts of tillage erosion is are simply not as visually ible as those caused by present as water erosion, which leads to rapid topographical dynamics (rills and gullys) and off-site damages (muddy floods, siltation). However, tillage erosion is a highly important soil redistribution process, taking place on the majority of sloped arable fields that urgently needs to be (re)drawn on the maps cientific consideration of the scientific community and implementation in soil conservation management by policy makers.

5 Conclusions

450

455

460

465

470

IWithin this study, ²³⁹⁺²⁴⁰Pu was used as a tracer to determine reconstruct soil redistribution in a hummocky young morainic study catchment under intense arable use. To understand the role of water and tillage erosion on soil degradation patterns, an inverse modelling approach was carried out in the study catchment. The results clearly show that recent soil degradation in the study area is dominated by tillage translocation. Furthermore, tillage erosion has a substantial impact on surface hydrology runoff. Tillage forms hydrological depressions at theas deposition at the downslope border between the cultivated field and the kettle hole that limits the edge between the field border and the kettle hole builds up hydrological depressions. These hydrological depressions limit the surface runoffhydrological and sedimentological connectivity into the kettle hole and force causes deposition of sediments that are transported by water. Soil redistribution by water has no major contribution to soil loss at on the catchment hillslopes of the catchment, but causes pronounced deposition in the spatially narrow area of the kettle hole surrounding flat. Within this study, soil erosion up to 17 cm (53 yr)⁻¹ and deposition exceeding 25 cm (53 yr)⁻¹ of recent morphodynamics geomorphological dynamics (since 1960s) were found. However, even these relatively high erosion rates cannot explain the current soil degradation patterns determined from soil prospection and chemical analysis that show both profile soil truncation and colluviation larger than one meter. This indicates that tillage erosion might is not be a process that exclusively takes place in highly mechanised agro-ecosystems but is potentially causing pronounced soil degradation in smallholder farming structures. Our results clearly underline that tillage erosion is a critically underrepresented soil degradation process that can be the main soil redistribution driver on catchment scale that takes place on the majority of sloped cultivated land.

Data availability

The data will be made available on request.

Author contribution

This paper represents a result of collegial teamwork. FW, PF and MS designed the sampling scheme. FW and SK carried out the field campaign. SK and FW prepared the soil samples for ²³⁹⁺²⁴⁰Pu activity analysis that were carried out by MK. Data

processing and analysis was done by FW. FW and PF prepared the manuscript. All authors read and approved the final manuscript.

Competing interest

The authors declare that they have no conflict of interest.

480 Acknowledgements

485

We gratefully acknowledge the support during fieldwork of Norbert Wypler, Lidia Völker and Christoph Kappler. Special thanks also go to the farm owner Bernd Sohn for his permission to carry out various types of measurements on his field in the Uckermark. The authors thank Olivier Evrard and an anonymous reviewer for their valuable comments and suggestions.

References

495

510

- Aguado, E., and Burt, J. E.: Understanding weather and climate, Pearson Education Inc., Glenview, 2015.
- Alewell, C., Meusburger, K., Juretzko, G., Mabit, L., and Ketterer, M. E.: Suitability of 239+240Pu and 137Cs as tracers for soil erosion assessment in mountain grasslands, Chemosphere, 103, 274-280, 10.1016/j.chemosphere.2013.12.016, 2014.
 - Alewell, C., Pitois, A., Meusburger, K., Ketterer, M., and Mabit, L.: Pu239+240 from "contaminant" to soil erosion tracer: Where do we stand?, Earth-Sci. Rev., 172, 107-123, 10.1016/j.earscirev.2017.07.009, 2017.
 - Alewell, C., Borrelli, P., Meusburger, K., and Panagos, P.: Using the USLE: Chances, challenges and limitations of soil erosion modelling, International Soil and Water Conservation Research, 7, 203-225, 10.1016/j.iswcr.2019.05.004, 2019.
 - Auerswald, K., Fiener, P., Martin, W., and Elhaus, D.: Use and misuse of the K factor equation in soil erosion modeling: An alternative equation for determining USLE nomograph soil erodibility values, Catena, 118, 220-225, 2014.
- Belyaev, V. R., Wallbrink, P. J., Golosov, V. N., Murray, A. S., and Sidorchuk, A. Y.: A comparison of methods for evaluating soil redistribution in the severely eroded Stavropol region, southern European Russia, Geomorphology, 65, 173-193, 10.1016/j.geomorph.2004.09.001, 2005.
 - BGR: Erodierbarkeit der Ackerböden durch Wasser in Deutschland, Bundesanstalt für Geowissenschaften und Rohstoffe, Hannover, 2014a.
- BGR: Erosivität der Niederschläge in Deutschland, Bundesanstalt für Geowissenschaften und Rohstoffe, 505 Hannover, 2014b.
 - Blume, H. P., Bruemmer, G. W., Horn, R., Kandeler, E., Koegel-Knabner, I., Kretzschmar, R., Stahr, K., and Wilke, B. M.: Scheffer/Schachtschabel Lehrbuch der Bodenkunde, Springer Spektrum, Berlin, Germany, 2016.
 - Boulyga, S. F., and Becker, J. S.: Isotopic analysis of uranium and plutonium using ICP-MS and estimation of burn-up of spent uranium in contaminated environmental samples, J. Anal. At. Spectrom., 17, 1143-1147, 10.1039/B202196J, 2002.
 - Calitri, F., Sommer, M., Norton, K., Temme, A., Brandova, D., Portes, R., Christl, M., Ketterer, M. E., and Egli, M.: Tracing the temporal evolution of soil redistribution rates in an agricultural landscape using Pu239+240 and Be-10, Earth Surf. Process. Landf., 44, 1783-1798, 10.1002/esp.4612, 2019.
- Cerdan, O., Govers, G., Le Bissonnais, Y., Van Oost, K., Poesen, J., Saby, N., Gobin, A., Vacca, A., Quinton, J., Auerswald, K., Klik, A., Kwaad, F. J. P. M., Raclot, D., Ionita, I., Rejman, J., Rousseva, S., Muxart, T., Roxo, M. J., and Dostal, T.: Rates and spatial variations of soil erosion in Europe: A study based on erosion plot data,
- Geomorphology, 122, 167-177, 10.1016/j.geomorph.2010.06.011, 2010.

 Chartin, C., Evrard, O., Salvador-Blanes, S., Hinschberger, F., Van Oost, K., Lefevre, I., Daroussin, J., and Macaire, J. J.: Quantifying and modelling the impact of land consolidation and field borders on soil redistribution in agricultural landscapes (1954-2009), Catena, 110, 184-195, 10.1016/j.catena, 2013.06.006, 2013.
- Ciampalini, R., Follain, S., and Le Bissonnais, Y.: LandSoil: A model for analysing the impact of erosion on agricultural landscape evolution, Geomorphology, 175, 25-37, 10.1016/j.geomorph.2012.06.014, 2012.
 - Deumlich, D.: Erosive Niederschläge und ihre Eintrittswahrscheinlichkeit im Norden Deutschlands, Meteorol. Z., 8, 155-161, 1999.
- Deumlich, D., Jha, A., and Kirchner, G.: Comparing measurements, Be-7 radiotracer technique and process-based erosion model for estimating short-term soil loss from cultivated land in Northern Germany, Soil and Water Research, 12, 177-186, 10.17221/124/2016-swr, 2017.
 - Dlugoß, V., Fiener, P., Van Oost, K., and Schneider, K.: Model based analysis of lateral and vertical soil C fluxes induced by soil redistribution processes in a small agricultural watershed, Earth Surf. Process. Landf., 37, 193-208, 10.1002/esp.2246, 2012.

- Evangeliou, N., Hamburger, T., Talerko, N., Zibtsev, S., Bondar, Y., Stohl, A., Balkanski, Y., Mousseau, T. A., and Moller, A. P.: Reconstructing the Chernobyl Nuclear Power Plant (CNPP) accident 30 years after. A unique database of air concentration and deposition measurements over Europe, Environ. Pollut., 216, 408-418, 10.1016/j.envpol.2016.05.030, 2016.
- Evrard, O., Chaboche, P.-A., Ramon, R., Foucher, A., and Laceby, J. P.: A global review of sediment source fingerprinting research incorporating fallout radiocesium (137Cs), Geomorphology, 362, 107103, https://doi.org/10.1016/j.geomorph.2020.107103, 2020. Fachbereichsstandard-DDR: Verfahren der Pflanzenproduktion, Bodenbearbeitung, Krumenbearbeitung, TGL 28°759/03, Akademie der Landwirtschaftswissenschaften, Berlin, 1985.
- Fiener, P., Dlugoß, V., and Van Oost, K.: Erosion-induced carbon redistribution, burial and mineralisation Is the episodic nature of erosion processes important?, Catena, 133, 282-292, 10.1016/j.catena.2015.05.027, 2015.
 Fiener, P., Wilken, F., Aldana-Jague, E., Deumlich, D., Gómez, J. A., Guzmán, G., Hardy, R. A., Quinton, J. N., Sommer, M., Van Oost, K., and Wexler, R.: Uncertainties in assessing tillage erosion How appropriate are our measuring techniques?, Geomorphology, 304, 214-225, https://doi.org/10.1016/j.geomorph.2017.12.031, 2018.
- Fiener, P., Wilken, F., and Auerswald, K.: Filling the gap between plot and landscape scale eight years of soil erosion monitoring in 14 adjacent watersheds under soil conservation at Scheyern, Southern Germany, Adv. Geosci., 48, 31-48, 10.5194/adgeo-48-31-2019, 2019.
 - Forstner, B., and Isermeyer, F.: Transformation of Agriculture in East Germany, in: Agriculture in Germany, edited by: Tangermann, S., DLG Verlag, Frankfurt a. Main, Germany, 61-90, 2000.
- Gerke, H. H., Koszinski, S., Kalettka, T., and Sommer, M.: Structures and hydrologic function of soil landscapes with kettle holes using an integrated hydropedological approach, J. Hydrol., 393, 123-132, 10.1016/j.jhydrol.2009.12.047, 2010.
 - Govers, G., Vandaele, K., Desmet, P., Poesen, J., and Bunte, K.: The role of tillage in soil redistribution on hillslopes, Eur. J. Soil Sci., 45, 469-478, 10.1111/j.1365-2389.1994.tb00532.x, 1994.
- Heckrath, G., Djurhuus, J., Quine, T. A., Van Oost, K., Govers, G., and Zhang, Y.: Tillage erosion and its effect on soil properties and crop yield in Denmark, J. Environ. Qual., 34, 312-324, 2005.
 - Hengl, T., and MacMillan, R. A.: Predictive soil mapping with R, OpenGeoHub foundation, Wageningen, Netherlands, 2019.
- Herbrich, M., Gerke, H. H., Bens, O., and Sommer, M.: Water balance and leaching of dissolved organic and inorganic carbon of eroded Luvisols using high precision weighing lysimeters, Soil Till. Res., 165, 144-160, 10.1016/j.still.2016.08.003, 2017.
 - Hu, Y., and Kuhn, N. J.: Aggregates reduce transport distance of soil organic carbon: Are our balances correct?, Biogeosciences, 11, 6209-6219, 10.5194/bg-11-6209-2014, 2014.
- Hu, Y. X., Berhe, A. A., Fogel, M. L., Heckrath, G. J., and Kuhn, N. J.: Transport-distance specific SOC distribution: Does it skew erosion induced C fluxes?, Biogeochemistry, 128, 339-351, 10.1007/s10533-016-0211-y, 2016.
 - IUSS: World reference base for soil resources 2014. Update 2015. International soil classification system for naming soils and creating legends for soil maps. World Soil Resources Reports No. 106, FAO, Rome, 2015.
- Kappler, C., Kaiser, K., Tanski, P., Klos, F., Fulling, A., Mrotzek, A., Sommer, M., and Bens, O.: Stratigraphy and age of colluvial deposits indicating Late Holocene soil erosion in northeastern Germany, Catena, 170, 224-245, 10.1016/j.catena.2018.06.010, 2018.
 - Kashparov, V. A., Ahamdach, N., Zvarich, S. I., Yoschenko, V. I., Maloshtan, I. M., and Dewiere, L.: Kinetics of dissolution of Chernobyl fuel particles in soil in natural conditions, J. Environ. Radioact., 72, 335-353, https://doi.org/10.1016/j.jenvrad.2003.08.002, 2004.

- Keller, T., Sandin, M., Colombi, T., Horn, R., and Or, D.: Historical increase in agricultural machinery weights enhanced soil stress levels and adversely affected soil functioning, Soil Till. Res., 194, 10.1016/j.still.2019.104293, 2019.
 - Kelley, J. M., Bond, L. A., and Beasley, T. M.: Global distribution of Pu isotopes and Np-237, Science of the Total Environment, 238, 483-500, 10.1016/s0048-9697(99)00160-6, 1999.
- Ketterer, M. E., Hafer, K. M., Link, C. L., Kolwaite, D., Wilson, J., and Mietelski, J. W.: Resolving global versus local/regional Pu sources in the environment using sector ICP-MS, J. Anal. At. Spectrom., 19, 241-245, 10.1039/b302903d, 2004.
 - Krasa, J., Dostal, T., Jachymova, B., Bauer, M., and Devaty, J.: Soil erosion as a source of sediment and phosphorus in rivers and reservoirs Watershed analyses using WaTEM/SEDEM, Environ. Res., 171, 470-483, https://doi.org/10.1016/j.envres.2019.01.044, 2019.
 - Lal, R., Ahmadi, M., and Bajracharya, R. M.: Erosional impacts on soil properties and corn yield on Alfisols in central Ohio, Land Degrad. Dev., 11, 575-585, 2000.

- Li, S., Lobb, D. A., Lindstrom, M. J., and Farenhorst, A.: Tillage and water erosion on different landscapes in the northern North American Great Plains evaluated using Cs137 technique and soil erosion models, Catena, 70, 493-505, 10.1016/j.catena.2006.12.003, 2007.
- Li, S., Lobb, D. A., Lindstrom, M. J., and Farenhorst, A.: Patterns of water and tillage erosion on topographically complex landscapes in the North American Great Plains, J. Soil Water Conserv., 63, 37-46, 2008.
 - Lust, M., and Realo, E.: Determination of dose rate from Chernobyl-derived radiocaesium in Estonian soil, J. Environ. Radioact., 112, 118-124, 10.1016/j.jenvrad.2012.05.021, 2012.
- Mabit, L., Meusburger, K., Fulajtar, E., and Alewell, C.: The usefulness of 137Cs as a tracer for soil erosion assessment: A critical reply to Parsons and Foster (2011), Earth-Sci. Rev., 127, 300-307, 10.1016/j.earscirev.2013.05.008, 2013.
 - Mabit, L., Benmansour, M., Abril, J. M., Walling, D. E., Meusburger, K., Iurian, A. R., Bernard, C., Tarjan, S., Owens, P. N., Blake, W. H., and Alewell, C.: Fallout Pb-210 as a soil and sediment tracer in catchment sediment
- budget investigations: A review, Earth-Sci. Rev., 138, 335-351, 10.1016/j.earscirev.2014.06.007, 2014.

 Matsunaga, T., and Nagao, S.: Environmental behavior of plutonium isotopes studied in the area affected by the Chernobyl accident, Humic Substances Research, 5/6, 19-33, 2009.
 - Meusburger, K., Mabit, L., Ketterer, M., Park, J. H., Sandor, T., Porto, P., and Alewell, C.: A multi-radionuclide approach to evaluate the suitability of Pu239+240 as soil erosion tracer, Science of the Total Environment, 566, 1489-1499, 10.1016/j.scitotenv.2016.06.035, 2016.
- 1489-1499, 10.1016/j.scitotenv.2016.06.035, 2016.
 Montanarella, L., Pennock, D. J., McKenzie, N., Badraoui, M., Chude, V., Baptista, I., Mamo, T., Yemefack, M., Aulakh, M. S., Yagi, K., Hong, S. Y., Vijarnsorn, P., Zhang, G. L., Arrouays, D., Black, H., Krasilnikov, P., Sobocka, J., Alegre, J., Henriquez, C. R., Mendonca-Santos, M. D., Taboada, M., Espinosa-Victoria, D., AlShankiti, A., AlaviPanah, S. K., Elsheikh, E. A. E., Hempel, J., Arbestain, M. C., Nachtergaele, F., and Vargas,
 R.: World's soils are under threat, Soil, 2, 79-82, 10.5194/soil-2-79-2016, 2016.
- Muramatsu, Y., Ruhm, W., Yoshida, S., Tagami, K., Uchida, S., and Wirth, E.: Concentrations of Pu-239 and Pu-240 and their isotopic ratios determined by ICP-MS in soils collected from the Chernobyl 30-km zone, Environ. Sci. Technol., 34, 2913-2917, 10.1021/es0008968, 2000.
- Nadeu, E., Gobin, A., Fiener, P., Van Wesemael, B., and Van Oost, K.: Modelling the impact of agricultural management on soil carbon stocks at the regional scale: the role of lateral fluxes, Global Change Biol., 21, 3181–3192, 10.1111/gcb.12889, 2015.
 - Nash, J. E., and Sutcliffe, J. V.: River flow forecasting through conceptual models: Part I. A discussion of principles, J. Hydrol., 10, 282-290, 10.1016/0022-1694(70)90255-6, 1970.
- Nie, X. J., Zhang, H. B., and Su, Y. Y.: Soil carbon and nitrogen fraction dynamics affected by tillage erosion, Scientific Reports, 9, 10.1038/s41598-019-53077-6, 2019.

- Oettl, I. K., Sommer, M., Wehrhan, M., Wilken, F., and Fiener, P.: Tillage erosion as main driver of in-field biomass patterns in an intensively used hummocky landscape, Agriculture, Ecosystems and Environment, (under review), 2020.
- Olson, K. R., Gennadiyev, A. N., Jones, R. L., and Chernyanskii, S.: Erosion patterns on cultivated and reforested hillslopes in Moscow region, Russia, Soil Sci. Soc. Am. J., 66, 193-201, 10.2136/sssaj2002.0193, 2002.
- Parsons, A. J., and Foster, I. D. L.: What can we learn about soil erosion from the use of 137Cs?, Earth-Sci. Rev., 108, 101-113, 2011.
 - Pebesma, E. J.: Mutivariable geostatistics in S: the gstat package, Comput. Geosci., 30, 683-691, 2004.
 - Pennock, D. J.: Terrain attributes, landform segmentation, and soil redistribution, Soil Till. Res., 69, 15-26, 2003.
- Pimentel, D., and Burgess, M.: Soil erosion threatens food production, Agriculture, 3, 443-463, 10.3390/agriculture3030443, 2013.
 - Porto, P., and Walling, D. E.: Using plot experiments to test the validity of mass balance models employed to estimate soil redistribution rates from 137Cs and 210Pb-ex measurements, Appl. Radiat. Isot., 70, 2451-2459, 10.1016/j.apradiso.2012.06.012, 2012.
- Quine, T. A., Desmet, P. J. J., Govers, G., Vandaele, K., and Walling, D. E.: A comparison of the roles of tillage and water erosion in landform development and sediment export on agricultural land near Leuven, Belgium, IAHS Publications, 224, 77-86, 1994.
 - R: A Language and Environment for Statistical Computing: https://www.R-project.org/, 2015.
- Renard, K. G., Foster, G. R., Weesies, G. A., McCool, D. K., and Yoder, D. C.: Predicting soil erosion by water:
- A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE), Agricultural Handbook 703, USDA-ARS, Washington DC, 1996.
 - Schimmack, W., Auerswald, K., and Bunzl, K.: Can 239+240Pu replace 137Cs as an erosion tracer in agricultural landscapes contaminated with Chernobyl fallout?, J. Environ. Radioact., 53, 41-57, 10.1016/S0265-931X(00)00117-X, 2001.
- Schwertmann, U., Vogl, W., and Kainz, M.: Bodenerosion durch Wasser Vorhersage des Abtrags und Bewertung von Gegenmaßnahmen, Ulmer Verlag, Stuttgart, 64 pp., 1990.
 - Sommer, M., Gerke, H. H., and Deumlich, D.: Modelling soil landscape genesis A "time split" approach for hummocky agricultural landscapes, Geoderma, 145, 480-493, 10.1016/j.geoderma.2008.01.012, 2008.
 - Tiessen, K. H. D., Lobb, D. A., Mehuys, G. R., and Rees, H. W.: Tillage erosion within potato production in Atlantic Canada: II Erosivity of primary and secondary tillage operations, Soil Till. Res., 95, 320-331,
 - 10.1016/j.still.2007.02.009, 2007a. Tiessen, K. H. D., Mehuys, G. R., Lobb, D. A., and Rees, H. W.: Tillage erosion within potato production systems in Atlantic Canada I. Measurement of tillage translocation by implements used in seedbed preparation, Soil Till. Res., 95, 308-319, 10.1016/j.still.2007.02.003, 2007b.
- Troegel, T., and Schulz, C.: Ergebnisse der Agrarstrukturerhebung 2016 für das Land Brandenburg, Zeitschrift für amtliche Statistik Berlin Brandenburg, 1, 44-60, 2018.
 - Van der Meij, W. M., Temme, A., Wallinga, J., Hierold, W., and Sommer, M.: Topography reconstruction of eroding landscapes A case study from a hummocky ground moraine (CarboZALF-D), Geomorphology, 295, 758-772, 10.1016/j.geomorph.2017.08.015, 2017.
- van der Meij, W. M., Reimann, T., Vornehm, V. K., Temme, A., Wallinga, J., van Beek, R., and Sommer, M.: Reconstructing rates and patterns of colluvial soil redistribution in agrarian (hummocky) landscapes, Earth Surf. Process. Landf., 44, 2408-2422, 10.1002/esp.4671, 2019.
 - Van Oost, K., Govers, G., and Desmet, P.: Evaluating the effects of changes in landscape structure on soil erosion by water and tillage, Landscape Ecol., 15, 577-589, 2000.
- Van Oost, K., Govers, G., and Van Muysen, W.: A process-based conversion model for caesium-137 derived erosion rates on agricultural land: An integrated spatial approach, Earth Surf. Process. Landf., 28, 187-207, 2003.


- Van Oost, K., Quine, T., Govers, G., and Heckrath, G.: Modeling soil erosion induced carbon fluxes between soil and atmosphere on agricultural land using SPEROS-C, in: Advances in soil science. Soil erosion and carbon dynamics, edited by: Roose, E. J., Lal, R., Feller, C., Barthes, B., and Stewart, B. A., CRC Press, Boca Raton, 37-51, 2005a.
- Van Oost, K., Van Muysen, W., Govers, G., Deckers, J., and Quine, T. A.: From water to tillage erosion dominated landform evolution, Geomorphology, 72, 193-203, 10.1016/j.geomorph.2005.05.010, 2005b.
- Van Oost, K., and Govers, G.: Tillage erosion, in: Soil erosion in Europe, edited by: Boardman, J., and Poesen, J., Wiley, Chichester, 599-608, 2006.
- Van Oost, K., Govers, G., De Alba, S., and Quine, T. A.: Tillage erosion: a review of controlling factors and implications for soil quality, Prog. Phys. Geog., 30, 443-466, 10.1191/0309133306pp487ra, 2006.
 - Van Rompaey, A. J. J., Verstraeten, G., Van Oost, K., Govers, G., and Poesen, J.: Modelling mean annual sediment yield using a distributed approach, Earth Surf. Process. Landf., 26, 1221-1236, 2001.
- Wallbrink, P. J., and Murray, A. S.: Use of radionuclides as indicators of erosion processes, Hydrol. Processes, 7, 680 297-304, 10.1002/hyp.3360070307, 1993.
 - Walling, D. E., Zhang, Y., and He, Q.: Models for deriving estimates of erosion and deposition rates from fallout radionuclide (caesium-137, excess lead-210, and beryllium-7) measurements and the development of user-friendly software for model implementation, Impact of soil conservation measures on erosion control and soil quality, Vienna, 2011, 11-33,
- 685 Wilken, F., Fiener, P., and Van Oost, K.: Modelling a century of soil redistribution processes and carbon delivery from small watersheds using a multi-class sediment transport model, Earth Surf. Dynam., 5, 113-124, 10.5194/esurf-5-113-2017, 2017a.
 - Wilken, F., Sommer, M., Van Oost, K., Bens, O., and Fiener, P.: Process-oriented modelling to identify main drivers of erosion-induced carbon fluxes, SOIL, 3, 83-94, 10.5194/soil-3-83-2017, 2017b.
- 690 Wilken, F., Baur, M., Sommer, M., Deumlich, D., Bens, O., and Fiener, P.: Uncertainties in rainfall kinetic energyintensity relations for soil erosion modelling, Catena, 171, 234-244, 10.1016/j.catena.2018.07.002, 2018.
 - Winnige, B.: Ergebnisse zur Bodenverlagerung durch Bearbeitungserosion in der Jungmoraenenlandschaft Nordostdeutschlands: Investigations of soil movement by tillage as a type of soil erosion in the young moraine soil Archives of Agronomy of Northeast Germany, and Soil Science. 10.1080/03650340410001663864, 2004.
- 695 Wolz, A.: The organisation of agricultural production in East Germany since World War II: Historical roots and present situation, Leibniz-Institut für Agrarentwicklung in Mittel- und Osteuropa (IAMO), Halle, Germany, 2013. Wysocka-Czubaszek, A., and Czubaszek, R.: Tillage erosion: The principles, controlling factors and main implications for future research, J. Ecol. Eng., 15, 150-159, 10.12911/22998993.1125470, 2014.
- Xu, Y. H., Pan, S. M., Wu, M. M., Zhang, K. X., and Hao, Y. P.: Association of plutonium isotopes with natural 700 soil particles of different size and comparison with 137Cs, Science of the Total Environment, 581, 541-549, 10.1016/j.scitotenv.2016.12.162, 2017.
- Zhao, P. Z., Li, S., Wang, E. H., Chen, X. W., Deng, J. F., and Zhao, Y. S.: Tillage erosion and its effect on spatial variations of soil organic carbon in the black soil region of China, Soil Till. Res., 178, 72-81,
- 705 10.1016/j.still.2017.12.022, 2018.

Tables

Table 1: Parametrisation of the inverse modelling approach.

Parameter	Standard value or range in inverse modelling	Iteration step	Unit	Source
USLE factors				
P	1.0		-	Standard value for soil management without specific soil conservation, e.g. contour ploughing
С	0.081		-	Calculated from crop rotation following the procedure of Schwertmann et al. (1990)
R	45		kJ m ⁻² mm h ⁻¹	From erosivity map of BGR (2014b)
K	25		kg m ² h m ⁻² MJ ⁻¹ mm ⁻¹	From soil map of BGR (2014a)
LS	variable		-	Calculated using 5 m DEM provided by the state of Brandenburg, Germany
Parameters varied during inverse modelling				
Factor changing the product of all USLE factors (water erosion strength)	0.12	0.1	-	
k_{til}	251000	25	kg m ⁻¹	
k_{tc}	25500	25	m	

Figures






Figure 1: (a) Topography and nested soil sampling scheme in the young morainic study area in northeast Germany. P1 to P10 indicate the locations for high-resolution depth profile sampling (see Fig. 3). (b) Idealized catena for soil landscapes in hummocky ground moraines; 1: Calcaric Regosol (extremely eroded), 2: Nudiargic Luvisol (strongly eroded), 3: Calcic Luvisol (non-eroded), 4: Gleyic-Colluvic Regosol (colluvial).




Figure 2: Semivariogram and semivariogram model fit of the ²³⁹⁺²⁴⁰Pu block kriging interpolation.




Figure 3: Depth distribution of ²³⁹⁺²⁴⁰Pu at different geomorphological positions. Locations P1 to P10 are given in Figure 1.





Figure 4: Distribution histogram of 5 m x 5 m interpolated ²³⁹⁺²⁴⁰Pu measurements in 20 classes with descriptive statistics.






Figure 5: Linear correlation between measured and modelled $^{239+240}$ Pu inventories redistributed by water ($kk_{tc}te$: 150, P-factor: 1) and tillage erosion (k_{til} : 350 kg m⁻¹; * = p-value < 0.001). (a) Point by point correlation on 5 m x 5 m resolution (n: 1699); (b) class aggregation according to $^{239+240}$ Pu derived soil redistribution. Minimum and maximum class n is 27 and 184, respectively. While the points and classes are calculated for a reference of 43 Bq m⁻², the trend lines display the offset sensitivity of different reference $^{239+240}$ Pu activities.




Figure 6: Inverse modelling of tillage and water erosion compared to $^{239+240}$ Pu derived soil redistribution. Three parameter combinations (tillage transport coefficient, k_{til} ; water transport capacity coefficient, $k_{tc}kte$; deviation in water erosion strength compared to reference parameterisation) are tested on their effect on the goodness_of_fit, represented by the MEF (model efficiency coefficient: perfect model fit = 1; model prediction as good as the mean = 0; model prediction worse than mean = <0).




Figure 7: The Figure consists of four parts: (a) Soil redistribution derived from $^{239+240}$ Pu top and subsoil measurements using 43 Bq m⁻² as the reference inventory; (b) geostatistically interpolated soil redistribution based on $^{239+240}$ Pu point measurements; (c) modelled tillage erosion with a tillage transport coefficient (k_{til}) of 350 kg m⁻¹; (d) modelled water erosion according to reference parameterization (ktc: 150; also see Table 1).